

<b>F4 BRUTALE 910 R Euro 3</b>	
<b>ENGINE</b>	
Type	Four cylinder, 4 stroke, 16 valve
Timing system	"D.O.H.C", radial valve
Total displacement	909 cm <sup>3</sup> (55.4 cu. in.)
Compression ratio	13:1
Starting	Electric
Bore x stroke	76,0 mm x 50,1 mm (2.99 in. x 1.97 in. )
Max. horse power - r.p.m. (at the crankshaft)	102.2 Kw - 139 HP at 11000 ( 105,8 Kw - 144 HP at 11000 with Racing exhaust system+power unit kit ) - Lim. 12000 r.p.m.
Max. torque - r.p.m.	96.0 Nm (9.8 Kgm) at 8000 r.p.m.
Cooling system	Cooling with separated liquid and oil radiators
Engine management system	"Weber Marelli" 5SM ignition - injection integrated system; induction discharge electronic ignition; sequential timed "Multipoint" electronic injection
Clutch	Wet, multi - disc
Gear Box	Cassette gearbox; six speed, constant mesh
Primary drive	50/79
Gear ratio	
First gear: Speed*	13/38 105,5 Km/h (65.5 mph) at 12000 r.p.m.
Second gear: Speed*	16/34 145,1 Km/h (90.1 mph) at 12000 r.p.m.
Third gear: Speed*	18/32 173,4 Km/h (107.7 mph) at 12000 r.p.m.
Fourth gear: Speed*	20/30 205,5 Km/h (127.6 mph) at 12000 r.p.m.
Fifth gear: Speed*	22/29 233,9 Km/h (145.2 mph) at 12000 r.p.m.
Sixth gear: Speed*	19/23 262,0 Km/h (162.7 mph) at 12000 r.p.m.
Final velocity ratio	15x43
<b>ELECTRICAL EQUIPMENT</b>	
Voltage	12 V
Alternator	650 W at 5000 r.p.m.
Battery	12 V - 9 Ah
<b>DIMENSIONS AND WEIGHT</b>	
Wheelbase	1410 mm (55.55 in.)
Overall length	2020 mm (79.59 in.)
Overall width	760 mm (29.94 in.)
Saddle height	805 mm (31.72 in.)
Min. ground clearance	135 mm (5.32 in.)
Trail	101,5 mm (4.00 in.)
Dry weight	185 Kg (407.9 lbs)
Fuel tank capacity	19 l (5.02 U.S. gal.) - reserve fuel: 4 l (1.05 U.S. gal. )
<b>PERFORMANCE</b>	
Maximum speed*	262 Km/h (162.7 mph)
<b>FRAME</b>	
Type	CrMo Steel tubular trellis (TIG welded)
Rear swing arm pivot plates: material	Aluminium alloy
<b>FRONT SUSPENSION</b>	
Type	"UPSIDE - DOWN" telescopic hydraulic fork with rebound-compression damping and spring preload adjustment
Rod dia.	50 mm (1.97 in.) with carbonitriding
Travel on leg axis	129 mm (5.07 in.)
<b>REAR SUSPENSION</b>	
Type	Progressive, single shock absorber with rebound and compression (High speed / Low speed) damping and spring preload
Single sided swing arm: materiale	Aluminium alloy
Wheel travel	120 mm (4.72 in.)
<b>BRAKE</b>	
Front brake	Double floating disc with Ø 320 mm (Ø 12.6 in.) diameter, with steel braking band and aluminium flange
Front brake caliper	Radial-type with 4 pistons - Ø 34 mm (Ø 1.34 in.)
Rear brake	Single steel disc with Ø 210 mm (Ø 8.27 in.) diameter
Rear brake caliper	With 4 pistons - Ø 25,4 mm (Ø 1.00 in.)
<b>RIM</b>	
Front: Material / size	Forged aluminium alloy 3.50 " x 17 "
Rear: Material / size	Forged aluminium alloy 6.00 " x 17 "
<b>TYRES</b>	
Front	120/70 - ZR 17 (58 W)
Rear	190/55 - ZR 17 (75 W)
<b>FAIRING</b>	
Material	Thermoplastic

\* = Top speed attained on closed course.

MV Agusta Motorcycles is committed to the constant improvement of our products. Therefore the information and technical characteristics of the vehicles are subject to change without notice.